STARTEK
ARCHITECTURAL LIGHTING

Product Features Matrix

Overview of our product features, configurations, mounting options, and available design choices.

Series	Mounting	Light Direction			Shielding						Distribution									Standard Lumen Range (lm/ft)	Design Options							
							Direct Drop				Direct					Indirect												
		Direct Only	Indirect Only	Direct/Indirect	Flush	Regress	0.5"	1.0"	1.5"	Lit Ends	Lambertian	Batwing	Wall Wash	Room Fill	Grazer	Lambertian	Batwing	Room Fill	Grazer	Consult factory for extended performance.	Continuous Runs - 6" Increments	Continuous Runs - 1/16" Increments	Patterns	Custom Finishes	Remote Power Box	Emergency Battery	Control Solutions	Damp Location
Beam	Surface	✦	-	-	✦	-	✦	✦	✦	✦	✦	✦	✦	-	-	-	-	-	-	Min. 100 Direct / 100 Indirect Max. 1400 Direct / 1400 Indirect	✦	✓	✦	✦	✓	✦	✦	✦
	Suspended	✦	-	✦	✦	-	✦	✦	✦	✦	✦	✦	✦	-	-	✦	✦	-	-		✦	✓	✦	✦	✓	✦	✦	✦
	Wall	✦	-	✦	✦	-	✦	✦	✦	✦	✦	✦	✦	-	-	✦	✦	-	-		✦	✓	✦	✦	✓	✦	✦	✦
	Recessed Drywall	✦	-	-	✦	-	✦	✦	✦	✦	✦	✦	✦	-	-	-	-	-	-		✦	✦	✦	✦	✓	✦	✦	✦
	Recessed Grid	✦	-	-	✦	✦	✦	✦	✦	✦	✦	✦	✦	-	-	-	-	-	-		✦	✦	✦	✦	✓	✦	✦	✦
	Perimeter	✦	-	-	✦	✦	-	-	-	-	✦	-	-	✦	-	-	-	-	-		✦	✦	✦	✦	✓	✦	✦	✦
Slim Beam	Surface	✦	-	-	✦	-	✦	✦	✦	✦	✦	✦	✦	-	✦	-	-	-	-	Min. 100 Direct / 100 Indirect Max. 1400 Direct / 1400 Indirect	✦	✓	✦	✦	✓	✦	✦	✦
	Suspended	✦	✦	✦	✦	-	✦	✦	✦	✦	✦	✦	✦	-	-	✦	✦	-	-		✦	✓	✦	✦	✓	✦	✦	✦
	Wall	✦	✦	✦	✦	-	✦	✦	✦	✦	✦	✦	✦	-	✦	✦	✦	-	-		✦	✓	✦	✦	✓	✦	✦	✦
	Recessed Drywall	✦	-	-	✦	-	✦	✦	✦	✦	✦	✦	✦	-	✦	-	-	-	-		✦	✦	✦	✦	✓	✦	✦	✦
	Recessed Grid	✦	-	-	✦	✦	✦	✦	✦	✦	✦	✦	✦	-	✦	-	-	-	-		✦	✦	✦	✦	✓	✦	✦	✦
	Perimeter	✦	-	-	✦	✦	-	-	-	-	✦	-	-	✦	✦	-	-	-	-		✦	✦	✦	✦	✓	✦	✦	✦
Tall Beam	Suspended	✦	-	✦	✦	-	-	-	-	-	✦	✦	✦	-	-	✦	✦	-	-	Min. 100 Direct / 100 Indirect Max. 1400 Direct / 1400 Indirect	✦	✓	✦	✦	✓	✦	✦	✦
	Wall	✦	-	✦	✦	-	-	-	-	-	✦	✦	✦	-	-	✦	✦	-	-		✦	✓	✦	✦	✓	✦	✦	✦
X-Beam	Suspended	✦	-	✦	-	✦	-	-	-	-	✦	✦	-	-	-	✦	✦	-	-		✦	-	-	✦	✓	✦	✦	✦
Clover	Surface	✦	-	-	✦	-	-	-	-	-	✦	✦	✦	-	-	-	-	-	-		✦	✓	-	✦	✓	✦	✦	✦
	Suspended	✦	-	✦	✦	-	-	-	-	-	✦	✦	✦	-	-	✦	✦	-	-		✦	✓	-	✦	✓	✦	✦	✦
Sculptura	Surface	✦	-	-	✦	-	-	-	-	-	✦	-	-	-	-	-	-	-	-	Min. 100 Direct / 100 Indirect Max. 1400 Direct / 1400 Indirect	-	-	✓	✦	✓	✦	✦	✦
	Suspended	✦	-	✦	✦	-	-	-	-	-	✦	-	-	-	-	✦	✦	-	-		-	-	✓	✦	✓	✦	✦	✦
	Wall	✦	-	✦	✦	-	-	-	-	-	✦	-	-	-	-	✦	✦	-	-		-	-	✓	✦	✓	✦	✦	✦
	Recessed Drywall	✦	-	-	✦	-	-	-	-	-	✦	-	-	-	-	-	-	-	-		-	-	-	✦	✓	✦	✦	✦
	Recessed Grid	✦	-	-	✦	-	-	-	-	-	✦	-	-	-	-	-	-	-	-		-	-	-	✦	✓	✦	✦	✦

LEGEND

✦ Standard StarTek option ✓ Available add-on - Unavailable

STARTEK Architectural Lighting
899 E. Park Avenue, Libertyville, Illinois 60048
877-782-7835

Updated 11/11/2026
The information in this document is subject to change without notice.
Contact STARTEK for most up to date product details.