STARTEK
ARCHITECTURAL LIGHTING

Rep/Agent		Type	
Project			
Order No.		Date	

Beam Flex Shape
Recessed



Key Features

- Extruded aluminum single piece housing
- Continuous lensing standard – runs up to 100'
- 2', 4', 6' and 8' individual units or continuous rows
- 0-10V dimming to 1% is standard
- Efficacy up to 130 lm/W
- Compatible with Armstrong Ceiling Systems and Slot Ceilings
- Consult factory for TM21, TM30, LM79 and LM80

5 Year Warranty · BABA Compliant · BAA Compliant · Intertek · DLC LISTED · RoHS Compliant · Declare.

Specifications

Construction

- Continuous extruded 6063 T5 aluminum

Dimensions

- Nominal dimensions: 3.5" x 3.5"
- Nominal thickness: 0.075"

Finish

- Powder coated
- Colors: White or Black
- Custom colors available. Consult factory for more information.

Luminaire Length

- Standard individual lengths: 2', 4', 6' or 8'
- Fixture and run lengths are available in $\frac{1}{16}$" increments.
- Using internal joiners, sections can be joined to form longer, continuous rows.
- Field Fit allows for field adjustments up to 6" to the overall run lengths.

Source

- CCT options: 2700K, 3000K, 3500K, 4000K, or 5000K
- Within 3 MacAdam ellipses, 90 CRI (R9 50 min) available, and L70 > 50,000 hours.

Lensing

- 0.060" thick impact resistant acrylic lens
- Snap-in lens and reflector for easy install

Operating Temperature

- -40°C to 45°C (-40°F to 113°F)

Lithium Ion Battery

- Provides up to 720 lm (6W) or up to 1200 lm (10W) for 90 minutes.
- Certifications: UL924 listed, Class 2 compliant, and Title 20 CEC (California Energy Commission) compliant

Dimming (Integral) Driver

- eldoLED OPTOTRONIC (OTi) series is UL Class 2 with tunable output currents.
- Output current: 0-10V, dim to 1%
- Overcurrent protection: 2.5KV ring/wave
- Power factor: >0.90
- THD: <20%
- Max load: 87% efficiency

Generator Transfer Device

- Luminaires with GTD option provides a UL924 shunt relay to bypass normal power, switches, and 0–10V dimming.

Certifications

- Build America Buy America compliant
- Buy American Act compliant
- Intertek cETLus Listed
- DLC listed
- RoHS (Restriction of Hazardous Substances)
- IC rated
- Chicago Plenum available
- JA8 compliant
- Suitable for dry and damp locations

Packaging

- Sustainably manufactured outside cardboard box and biodegradable, protective poly-foam luminaire inserts.

Warranty

- 5-year limited warranty.

The information in this document is subject to change without notice.
Contact STARTEK for most up to date product details.

Ordering Logic

RBFLEX-4X6RECT-500-SD-35K-80-PW-FTG5-U-1C-2EMB10

Series	Length[1]	Direct Output[2]	Direct Distribution	CCT	CRI
RBFLEX					
	_X_RECT - Rectangle	**250 -** 250 LPF	**SD -** SatinIce Diffuse	**27K -** 2700K	**80 -** 80 CRI
	_X_L - L-Shape	**500 -** 500 LPF	**WD -** Wide Diffuse	**30K -** 3000K	**90 -** 90 CRI (R9 50 min)
	_X_X_U - U-Shape	**750 -** 750 LPF	**WW -** Wall Wash	**35K -** 3500K	
		1000 - 1000 LPF	**GRZ -** Wall Graze	**40K -** 4000K	
		XXX - Custom LPF		**50K -** 5000K	
				TW - Tunable White[3] (2700K-6500K)	

Finish[4]	Mounting[5]	Voltage	Circuiting	Emergency
Standard Powder Coat	**Flush T-Grid Bezel**	**U -** 120-277V	**1C -** Single Circuit	**BLANK -** None
PW - White	**FTG5 -** 5" O.C.	**C -** 347V	**MC -** Multiple Circuits[7, 8]	**EC -** Emergency Circuit[11]
PB - Black	**FTG6 -** 6" O.C.		**DL -** Daylight Control[7, 9]	**#EMB6 -** 6W EM Battery[12, 13]
Premium	**FTGX -** X" O.C.[6]		**NL -** Night Lights[7, 10]	**#EMB10 -** 10W EM Battery[12, 13]
RALXXXX - Powder Coat Gloss Finish				**#FCEMB10 -** 10W EM Battery[12, 14]
Custom Powder Coat				**#FCEMB14 -** 14W EM Battery[12, 14]
PO - Powder Other				**#GTD -** Generator Transfer Device w/ ALCR[15]

Options

Specialty Drivers[16]	Sensors
DT1 - eldoLED EcoDrive Dim to 1% (0-10V)	**DMXX% -** Daylight/Motion Sensor (XX%=% Min. Dimming)
DTZ - eldoLED SoloDrive Dim to 0.1% (0-10V)	**VDO -** Lutron Vive Integral Fixture Control (RF w/ Daylight and Occupancy)
PSRD - Philips Sensor Ready (DALI) Driver	**AWNR -** Lutron Athena Wireless Node (RF Only)[20]
LDE1 - Lutron Hi-Lume EcoSystem LED Driver w/ Soft-on, Fade-to-Black	**AWNS -** Lutron Athena Wireless Node w/ Sensor[20]
TW-A - Tunable White, 0-10V[17]	**NLA -** Acuity nLight Air[19]
TW-EL - eldoLED DUALdrive Tunable White (DALI)[17]	**NLW -** Acuity nLight Wired[19]
LD2 - Lutron DALI 2 Digital Tunable White Driver w/ 1% Dimming[18]	**WVL -** Cooper Wavelinx[19]
HD-XX - HyperDrive Remote Driver[19]	


Ordering Notes

1. Replace underscore (_) with fixture leg length. See page 8.
2. 200 LPF min. output / 1500 LPF max. output.
3. Tunable White Driver must be specified in options.
4. See page 3 for standard options.
5. Bezel color will match fixture color unless otherwise specified, consult factory for options.
6. Replace 'X' with specified grid center dimension.
7. Customer to specify number of zones and locations through factory submittal drawings.
8. Multiple low and line control zones.
9. Multiple low voltage control zones for daylight control.
10. Multiple unswitched wires for night light control zones.
11. Separate power, transfer devices provided by others.
12. '#' indicates number per run.
13. Provided by Iota/Bodine.
14. EM battery is factory choice.
15. Iota EDS-DR Emergency Control Device
16. Standard driver is 0-10V, dim to 1% output current.
17. 75 Watt Max. Dual driver required for higher fixture wattage.
18. 50 Watt Max. Dual driver required for higher fixture wattage.
19. Consult factory.
20. Athena sensor matches finish for white and black fixtures.


The information in this document is subject to change without notice.
Contact STARTEK for most up to date product details.

Dimensions

Angled T-Grid Bezel (ATG)



Flush T-Grid Bezel (FTG)




Finishes

Standard


PW: White

PB: Black


Distribution




Direct: SatinIce Diffuse (SD)



Direct: Wide Diffuse (WD)




Direct: Wall Wash (WW)



Direct: Wall Graze (GRZ)


Performance

RBFLEX-X-1000-SD (80+ CRI)



CCT	Length	Lumens	Wattage	LPW
3000K	4'	4000	35	115
	8'	8000	67	119
3500K	4'	4000	34	118
	8'	8000	65	122
4000K	4'	4000	33	121
	8'	8000	64	125
5000K	4'	4000	32	126
	8'	8000	62	130

RBFLEX-X-1000-WW (80+ CRI)




CCT	Length	Lumens	Wattage	LPW
3000K	4'	4000	33	123
	8'	8000	63	127
3500K	4'	4000	32	126
	8'	8000	62	130
4000K	4'	4000	31	129
	8'	8000	60	133
5000K	4'	4000	30	134
	8'	8000	58	138


Mounting

Flush Bezel T-Grid (FTG)


Designed to work with grid heights of 1-1/2", 1-11/16", and 1-3/4" in Flush configuration, and 1-1/2" & 1-11/16" for Tegular tile configurations. Please refer to "FTGX" if another configuration is desired or consult factory.




9/16" T-Bar




15/16" T-Bar




FTGX




9/16" T-Bar



15/16" T-Bar





The information in this document is subject to change without notice.
Contact STARTEK for most up to date product details.


Shape Configuration

Joint Shape

Example: Standard 24" x 24" joint configurations are provided as a single piece per image below.


Rectangle (_X_RECT)

Provide AxB dimensions




L-Shape (_X_L)

Provide AxB dimensions



U-Shape (_X_X_U)

Provide AxB dimensions




Power Location


2' x 2' Corner

Controls

Sensor

Wattstopper FS-205 v2 Low Voltage PIR. Integrated photosensor for hold-off daylighting control. 24VDC operating voltage. Adjustable time delay (30 seconds to 30 minutes).







Wireless Node

