


Sculptura Wall

Direct

Key Features

- Extruded aluminum single piece housing
- Seamless glare eliminating shade
- Light levels can be factory set
- 0-10V dimming to 1% is standard
- Efficacy up to 130 lm/W with UGR <19
- Consult factory for TM21, TM30, LM79 and LM80



Specifications

Construction

- Continuous extruded 6063 T5 aluminum
- Mechanically attached end caps with no exposed fasteners enhance architectural aesthetic and prevent light leak.

Dimensions

- Nominal dimensions: 2.0" x 3.5"
- Nominal thickness: 0.075"

Finish

- Powder coated
- Colors: White, Black, Silver or Premium Finishes
- End Caps: Color-matched to housing
- Custom colors available. Consult factory for more information.

Luminaire Length

- Standard individual lengths: 2', 4', 6' or 8'
- Using internal joiners, sections can be joined to form longer, continuous rows.

Source

- CCT options: 2700K, 3000K, 3500K, 4000K, or 5000K
- All within 3 MacAdam ellipses
- 90 CRI (R9 50 min) available

Lensing

- Diffused polymethyl methacrylate (PMMA) shades with matte finish.

Operating Temperature

- -40°C to 50°C (-40°F to 122°F)

Lithium Ion Battery

- Provides up to 780 lm (6W) or up to 1300 lm (10W) for 90 minutes.
- Certifications: UL924 listed, Class 2 compliant, and Title 20 CEC (California Energy Commission) compliant

Dimming (Integral) Driver

- Constant current programmable LED driver
- Output current: 0-10V, dim to 1% (UL listed, Class P)
- Ring wave surge protection: 2.5KV ring
- Power factor: >0.90

Generator Transfer Device

- Luminaires with GTD option provides a UL924 shunt relay to bypass normal power, switches, and 0-10V dimming.

Certifications

- Build America Buy America compliant
- Buy American Act compliant
- Intertek cETLus Listed
- RoHS (Restriction of Hazardous Substances)
- JA8 compliant
- Suitable for dry and damp locations

Packaging

- Sustainably manufactured outside cardboard box and biodegradable, protective poly-foam luminaire inserts.

Warranty

- 5-year limited warranty.



Ordering Logic

SCULPTD-40-750-B50-35K-80-PB-WM-U-1C-1EMB10

Series	Length	Direct Output ¹	Direct Distribution	CCT	CRI
SCULPTD					
	XX - Run Length	250 - 250 LPF	50° Reflector	27K - 2700K	80 - 80 CRI
	SXX - Symmetrical Run Length	500 - 500 LPF	B50 - Black Reflector	30K - 3000K	90 - 90 CRI (R9 50 min)
		750 - 750 LPF	W50 - White Reflector	35K - 3500K	
		1000 - 1000 LPF	S50 - Silver Reflector	40K - 4000K	
	XXX - Custom LPF		80° Reflector	50K - 5000K	
			B80 - Black Reflector	TW - Tunable White ² (2700K-6500K)	
			W80 - White Reflector		
			S80 - Silver Reflector		

Finish ³	Mounting	Voltage	Circuiting	Emergency
Standard Powder Coat	WM - Wall Mount	U - 120-277V	1C - Single Circuit	BLANK - None
PW - White	AWM - Architectural Wall Mount	C - 347V	MC - Multiple Circuits ^{5, 6}	EC - Emergency Circuit ⁹
PB - Black	EWMXX - Extruded Wall Mount, XX ⁴		DL - Daylight Control ^{5, 7}	#EMB6 - 6W EM Battery ^{10, 11}
PS - Silver			NL - Night Lights ^{5, 8}	#EMB10 - 10W EM Battery ^{10, 11}
Premium				#FCEMB10 - 10W EM Battery ^{10, 12}
RALXXXX - Powder Coat Gloss Finish				#FCEMB14 - 14W EM Battery ^{10, 12}
PSFX - Premium Stock Finish				#GTD - Generator Transfer Device w/ ALCR ¹³
Custom Powder Coat				
PO - Powder Other				

Options

Specialty Drivers¹⁴

- DT1** - eldoLED EcoDrive Dim to 1% (0-10V)
- DTZ** - eldoLED SoloDrive Dim to 0.1% (0-10V)
- PSRD** - Philips Sensor Ready (DALI) Driver
- LDE1** - Lutron Hi-Lume EcoSystem LED Driver w/ Soft-on, Fade-to-Black
- TW-A** - Tunable White, 0-10V¹⁵
- TW-EL** - eldoLED DUALdrive Tunable White (DALI)¹⁵
- LD2** - Lutron DALI 2 Digital Tunable White Driver w/ 1% Dimming¹⁶
- HD-XX** - HyperDrive Remote Driver¹⁷


Sensors

- DMXX%** - Daylight/Motion Sensor (XX%-% Min. Dimming)
- VDO** - Lutron Vive Integral Fixture Control (RF w/ Daylight and Occupancy)
- AWNRR** - Lutron Athena Wireless Node (RF Only)¹⁸
- AWNS** - Lutron Athena Wireless Node w/ Sensor¹⁸
- NLA** - Acuity nLight Air¹⁷
- NLW** - Acuity nLight Wired¹⁷
- WVL** - Cooper Wavelinx¹⁷

Ordering Notes

- 200 LPF min. output / 1500 LPF max. output.
- Tunable White Driver must be specified in options.
- See page 3 for standard and premium options.
- 3' standard EWM. Custom sizes available up to 12'.
- Customer to specify number of zones and locations through factory submittal drawings.
- Multiple low and line control zones.
- Multiple low voltage control zones for daylight control.
- Multiple unswitched wires for night light control zones.
- Separate power, transfer devices provided by others.
- '#' indicates number per run.
- Provided by Iota/Bodine.
- EM battery is factory choice.
- [Iota EDS-DR Emergency Control Device](#)
- Standard driver is 0-10V, dim to 1% output current.
- 75 Watt Max. Dual driver required for higher fixture wattage.
- 50 Watt Max. Dual driver required for higher fixture wattage.
- Consult factory.
- Athena sensor matches finish for white and black fixtures.

Dimensions




Lumen Packages

Length	Lumens	Input Wattage	LPW
4'	3000	27	113
8'	6000	52	120

NOTE: Based on 3500K CCT. Other CCT available.

Finishes

Standard



PW: White



PB: Black



PS: Silver

Premium Stock




PSF001: Wood 1




PSF002: Wood 2



PSF003: Wood 3



PSF004: Wood 4



PSF005: Wood 5



PSF006: Wood 6



PSF007: Stone 1




PSF008: Stone 2




PSF009: Stone 3

NOTE: A minimal impact to lead times will apply to products specified with Premium Stock Finishes (PSF). It is not to be assumed that these finishes are stocked in our warehouse, but rather, are readily available to us for your project.
All other custom finishes (PO) will incur a set up fee and will add an extended lead time to your project.

Distribution




Direct: 50° Reflector



Direct: 80° Reflector


Performance

SCULPTD-X-750-B50-35K (80+ CRI)



CCT	Length	Lumens	Wattage	LPW
3000K	4'	3000	27	110
	8'	6000	51	117
3500K	4'	3000	27	113
	8'	6000	50	120
4000K	4'	3000	26	116
	8'	6000	49	123
5000K	4'	3000	25	120
	8'	6000	37	127

SCULPTD-X-750-B80-35K (80+ CRI)



CCT	Length	Lumens	Wattage	LPW
3000K	4'	3000	27	113
	8'	6000	50	120
3500K	4'	3000	26	116
	8'	6000	49	123
4000K	4'	3000	25	119
	8'	6000	48	126
5000K	4'	3000	24	123
	8'	6000	46	130

Row Configurations

XX (Run Length)

The standard construction of run lengths follows the logic of the table below. Consult factory for additional information. Run lengths always start with the longest fixture and receives the power feed.

NOTE: Fixtures in continuous runs are available in 6" increments. Consult factory for smaller increments.

Total Length (Feet)	# of Sections						
	2	3	4	5	6	7	8
2	1						
3		1					
4			1				
5				1			
6					1		
7						1	
8							1
9			1	1			
10			1		1		
11		1					1
12			1				1
13				1			1
14					1		1
15						1	1
16							2
17			1	1			1
18			1		1		1
19		1					2
20			1				2
21				1			2
22					1		2
23						1	2
24							3
25			1	1			2
26			1		1		2
27		1					3
28			1				3
29				1			3
30					1		3
31						1	3
32							4
33			1	1			3
34			1		1		3
35		1					4
36			1				4
37				1			4
38					1		4
39						1	4
40							5

SXX (Symmetric Run)



The construction of SXX (y') is to build with equal length fixtures. The xx indicates the run length. The y' indicates the fixture length used to create the run. Please indicate this on your P.O. when placing your order.

S12' (2')	2'	2'	2'	2'	2'	2'
S12' (3')	3'	3'	3'	3'		
S12' (4')	4'	4'	4'			
S12' (6')	6'	6'				

Mounting



WM (Wall Mount)

Standard Power Location
Consult Factory for Custom Locations






AWM (Architectural Wall Mount)

Power Wires Located at
Center of Fixture



EWM (Extruded Wall Mount)



Mounting Locations

Each starter or individual fixture will be provided with (2) mounting supports (●). Each additional fixture will be provided with (1) support which can be located anywhere along the second half of the fixture (highlighted below):


Examples of continuous run mounting locations are as follows:

12' Run	●	8'	●	4'
16' Run	●	8'	●	8'
20' Run	●	8'	●	8'
24' Run	●	8'	●	8'
28' Run	●	8'	●	8'

Controls

Sensor

Wattstopper FS-205 v2 Low Voltage PIR. Integrated photosensor for hold-off daylighting control.
24VDC operating voltage. Adjustable time delay (30 seconds to 30 minutes).



Wireless Node

