


Sculptura Wall

Direct / Indirect

Key Features

- Extruded aluminum single piece housing
- Seamless glare eliminating shade
- Light levels can be factory set
- 0-10V dimming to 1% is standard
- Efficacy up to 137 lm/W with UGR <19
- Consult factory for TM21, TM30, LM79 and LM80



Specifications

Construction

- Continuous extruded 6063 T5 aluminum
- Mechanically attached end caps with no exposed fasteners enhance architectural aesthetic and prevent light leak.

Dimensions

- Nominal dimensions: 2.0" x 3.5"
- Nominal thickness: 0.075"

Finish

- Powder coated
- Colors: White, Black, Silver or Premium Finishes
- End Caps: Color-matched to housing
- Custom colors available. Consult factory for more information.

Luminaire Length

- Standard individual lengths: 2', 4', 6' or 8'
- Using internal joiners, sections can be joined to form longer, continuous rows.

Source

- CCT options: 2700K, 3000K, 3500K, 4000K, or 5000K
- All within 3 MacAdam ellipses
- 90 CRI (R9 50 min) available

Lensing

- Diffused polymethyl methacrylate (PMMA) shades with matte finish.

Operating Temperature

- -40°C to 50°C (-40°F to 122°F)

Lithium Ion Battery

- Provides up to 780 lm (6W) or up to 1300 lm (10W) for 90 minutes.
- Certifications: UL924 listed, Class 2 compliant, and Title 20 CEC (California Energy Commission) compliant

Dimming (Integral) Driver

- Constant current programmable LED driver
- Output current: 0-10V, dim to 1% (UL listed, Class P)
- Ring wave surge protection: 2.5KV ring
- Power factor: >0.90

Generator Transfer Device

- Luminaires with GTD option provides a UL924 shunt relay to bypass normal power, switches, and 0-10V dimming.

Certifications

- Build America Buy America compliant
- Buy American Act compliant
- Intertek cETLus Listed
- RoHS (Restriction of Hazardous Substances)
- JA8 compliant
- Suitable for dry and damp locations

Packaging

- Sustainably manufactured outside cardboard box and biodegradable, protective poly-foam luminaire inserts.

Warranty

- 5-year limited warranty.



Ordering Logic

SCULPTDI-40-500-750-B50-BW-35K-90-PW-WM-U-1C-1EMB10

Series	Length	Direct Output ¹	Indirect Output ¹	Direct Distribution	Indirect Distribution
SCULPTDI					
	XX - Run Length	250 - 250 LPF	250 - 250 LPF	50° Reflector	CL - Clear Lens
	SXX - Symmetrical Run Length	500 - 500 LPF	500 - 500 LPF	B50 - Black Reflector	BW - Batwing
		750 - 750 LPF	750 - 750 LPF	W50 - White Reflector	ID - Indirect Diffuse
		1000 - 1000 LPF	1000 - 1000 LPF	S50 - Silver Reflector	
	XXX - Custom LPF	XXX - Custom LPF	XXX - Custom LPF	80° Reflector	
				B80 - Black Reflector	
				W80 - White Reflector	
				S80 - Silver Reflector	


CCT	CRI	Finish ³	Mounting	Voltage	Circuiting
27K - 2700K	80 - 80 CRI	Standard Powder Coat	WM - Wall Mount	U - 120-277V	1C - Single Circuit
30K - 3000K	90 - 90 CRI (R9 50 min)	PW - White	AWM - Architectural Wall Mount	C - 347V	2C - Separate D/I Circuits ⁵
35K - 3500K		PB - Black	EWMXX - Extruded Wall Mount, XX ⁴		MC - Multiple Circuits ^{6,7}
40K - 4000K		PS - Silver			DL - Daylight Control ^{8,9}
50K - 5000K		Premium			NL - Night Lights ^{6,9}
TW - Tunable White ² (2700K-6500K)		RALXXXX - Powder Coat Gloss Finish			
		PSFX - Premium Stock Finish			
		Custom Powder Coat			
		PO - Powder Other			

Emergency	Options	
BLANK - None	Specialty Drivers¹⁵	Sensors
EC - Emergency Circuit ¹⁰	DT1 - eldoLED EcoDrive Dim to 1% (0-10V)	DMXX% - Daylight/Motion Sensor (XX%-% Min. Dimming)
#EMB6 - 6W EM Battery ^{11,12}	DTZ - eldoLED SoloDrive Dim to 0.1% (0-10V)	AWNRR - Lutron Athena Wireless Node (RF Only) ¹⁹
#EMB10 - 10W EM Battery ^{11,12}	PSRD - Philips Sensor Ready (DALI) Driver	AWNS - Lutron Athena Wireless Node w/ Sensor ¹⁹
#FCEMB10 - 10W EM Battery ^{11,13}	LDE1 - Lutron Hi-Lume EcoSystem LED Driver w/ Soft-on, Fade-to-Black	NLA - Acuity nLight Air ¹⁸
#FCEMB14 - 14W EM Battery ^{11,13}	TW-A - Tunable White, 0-10V ¹⁶	NLW - Acuity nLight Wired ¹⁸
#GTD - Generator Transfer Device w/ ALCR ¹⁴	TW-EL - eldoLED DUALdrive Tunable White (DALI) ¹⁶	WVL - Cooper Wavelinx ¹⁸
	LD2 - Lutron DALI 2 Digital Tunable White Driver w/ 1% Dimming ¹⁷	
	HD-XX - HyperDrive Remote Driver ¹⁸	

Ordering Notes

- 200 LPF min. output / 1500 LPF max. output.
- Tunable White Driver must be specified in options.
- See page 3 for standard and premium options.
- 3" standard EWM. Custom sizes available up to 12".
- Separate D/I switched power and dimming (shared neutral).
- Customer to specify number of zones and locations through factory submittal drawings.
- Multiple low and line control zones.
- Multiple low voltage control zones for daylight control.
- Multiple unswitched wires for night light control zones.
- Separate power, transfer devices provided by others.
- '#' indicates number per run.
- Provided by Iota/Bodine.
- EM battery is factory choice.
- Iota EDS-DR Emergency Control Device
- Standard driver is 0-10V, dim to 1% output current.
- 75 Watt Max. Dual driver required for higher fixture wattage.
- 50 Watt Max. Dual driver required for higher fixture wattage.
- Consult factory.
- Athena sensor matches finish for white and black fixtures.

Dimensions




Reflectors



Black
50° or 80°



White
50° or 80°



Silver
50° or 80°

Finishes

Standard



PW: White



PB: Black



PS: Silver

Premium Stock




PSF001: Wood 1




PSF002: Wood 2



PSF003: Wood 3



PSF004: Wood 4



PSF005: Wood 5



PSF006: Wood 6



PSF007: Stone 1



PSF008: Stone 2




PSF009: Stone 3


NOTE: A minimal impact to lead times will apply to products specified with Premium Stock Finishes (PSF). It is not to be assumed that these finishes are stocked in our warehouse, but rather, are readily available to us for your project.

All other custom finishes (PO) will incur a set up fee and will add an extended lead time to your project.


Distribution




Indirect: Clear (CL)
Direct: 50° Reflector



Indirect: Batwing (BW)
Direct: 80° Reflector



Indirect: Clear (CL)
Direct: 50° Reflector




Indirect: Batwing (BW)
Direct: 80° Reflector




Performance

SCULPTDI-X-350-750-B80-BW (80+ CRI)




CCT	Length	Lumens	Wattage	LPW
3000K	4'	4400	37	120
	8'	8800	69	127
3500K	4'	4400	36	123
	8'	8800	68	130
4000K	4'	4400	35	126
	8'	8800	66	133
5000K	4'	4400	34	130
	8'	8800	64	137

SCULPTDI-X-500-500-B80-BW (80+ CRI)



CCT	Length	Lumens	Wattage	LPW
3000K	4'	4000	34	119
	8'	8000	63	126
3500K	4'	4000	33	122
	8'	8000	62	129
4000K	4'	4000	32	125
	8'	8000	61	132
5000K	4'	4000	31	129
	8'	8000	59	136

SCULPTDI-X-750-350-B50-CL (80+ CRI)



CCT	Length	Lumens	Wattage	LPW
3000K	4'	4400	38	110
	8'	8800	72	117
3500K	4'	4400	37	113
	8'	8800	70	120
4000K	4'	4400	36	116
	8'	8800	69	123
5000K	4'	4400	35	120
	8'	8800	67	127



Row Configurations

XX (Run Length)

The standard construction of run lengths follows the logic of the table below. Consult factory for additional information. Run lengths always start with the longest fixture and receives the power feed.

NOTE: Fixtures in continuous runs are available in 6" increments. Consult factory for smaller increments.

Total Length (Feet)	# of Sections						
	2	3	4	5	6	7	8
2	1						
3		1					
4			1				
5				1			
6					1		
7						1	
8							1
9			1	1			
10			1		1		
11		1					1
12			1				1
13				1			1
14					1		1
15						1	1
16							2
17			1	1			1
18			1		1		1
19		1					2
20			1				2
21				1			2
22					1		2
23						1	2
24							3
25			1	1			2
26			1		1		2
27		1					3
28			1				3
29				1			3
30					1		3
31						1	3
32							4
33			1	1			3
34			1		1		3
35		1					4
36			1				4
37				1			4
38					1		4
39						1	4
40							5

SXX (Symmetric Run)



The construction of SXX (y') is to build with equal length fixtures. The xx indicates the run length. The y' indicates the fixture length used to create the run. Please indicate this on your P.O. when placing your order.

S12' (2')	2'	2'	2'	2'	2'	2'
S12' (3')	3'	3'	3'	3'		
S12' (4')	4'	4'	4'			
S12' (6')	6'	6'				

Mounting



WM (Wall Mount)

Standard Power Location
Consult Factory for Custom Locations






AWM (Architectural Wall Mount)

Power Wires Located at
Center of Fixture



EWM (Extruded Wall Mount)



Mounting Locations

Each starter or individual fixture will be provided with (2) mounting supports (●). Each additional fixture will be provided with (1) support which can be located anywhere along the second half of the fixture (highlighted below):


Examples of continuous run mounting locations are as follows:

12' Run	●	8'	●	4'
16' Run	●	8'	●	8'
20' Run	●	8'	●	8'
24' Run	●	8'	●	8'
28' Run	●	8'	●	8'

Controls

Sensor

Wattstopper FS-205 v2 Low Voltage PIR. Integrated photosensor for hold-off daylighting control.
24VDC operating voltage. Adjustable time delay (30 seconds to 30 minutes).



Wireless Node

